85M SSV



GENERAL DATA

NEW BUILDING Year Built

Builder Design KHIAM CHUAN MARINE PTE LTD

85M SSV

Type Flag Registry Port HULL NO. Call Sign

Classification

ABS Class Character ABS + A1(E) RW, OFFSHORE

and Notations SUPPORT VESS (SUPPLY-HNLS,

FFV1) ,SPS, HDC (7.5t/m2,MAIN DK.), + AMS, ACCU + DPS-2,

HELIDK, CRC

MAIN DIMENSIONS

L.O.A. 85M 22.00M B. Mld. D. Mld. M8 Draft Load 6.3M Draft Light ~4.9m Gross Tonnage 4939 Deadweight 3049

PERFORMANCE

Maximum Speed 12.5knots at 5.9m

ACCOMMODATION

Crew

Passenger Special Person: 176

MACHINERY & PROPULSION

Main Engine Niigata 6L28AHX 2x3000HP Horsepower 2x4 blades F.P.P Propeller

Generator Sets Auxiliary Generator :

3x830KW Caterpillar Shaft Generator: 2x1500KW Leroy Somer

Emergency Generator:

192KW Cummins CCFJ192Y-KC

Bow Thruster 2x12T Kawasaki

Stern Thruster N/A

DECK EQUIPMENT

Capstan 2x10T at 15m/min Tugger 2x10T at 15m/min

4-Point Mooring 4x40T at 10m/min Winch Main Crane 100T at 15m Service Crane 3T at 14m

SAFETY & FIFI & ANTIPOLLUTION EQUIPMENT

Life Raft 8x25 Persons; Life & Rescue Boat 2x75 Persons

FiFi 2x2200cu.m/hr

DECK CAPACITIES

Deck Area 740 sq.m Deck Cargo T008 7.5T/sq.m Deck Loading

CARGO CAPACITIES

Fresh Water 744 cu.m Drill Water 1750 cu.m HEEL. Water 450 cu.m Ballast Water 280 cu.m Fuel Oil 1160 cu.m Bulk 226 m3 Liquid Mud/Brine 730 cu.m Mud 415 cu.m

DISCHARGING RATES

150 cu.m/hr at 0.75 MPa P. Water

D./B. Water 150 cu.m/hr at 0.75 MPa 200cu.m/hr at

1.0 MPa

Diesel Oil 2x150 cu.m/hr at 0.75 MPa Bulk 2x30 cu.m/hr at 0.56 MPa Liquid Mud 2x70 cu.m/hr at 0.85 MPa Brine 2x70 cu.m/hr at 0.85 MPa